

RADIOTRONICS

Technical Bulletins 1941

INDEX

	Page		Page
Amplifier, 13 watt 6V6-G (A504)	31-35	Phototube Characteristics	11-13, 14
Amplifier, 4.5 watt, with tone control (A505)	51	Preamplifier and mixer considerations	57
Audibility: Results of hearing tests	21	Preamplifiers, battery operated	59
Audio amplifiers, frequency compensation in	43	Preamplifier circuit using 1603	20
Australian-made Radiotrons, complete list of	50	Q Meter, measurement of damping using	38
Australian-made Transmitting Valves, out- put of	50	Radio frequency amplifiers, lower grid bias for	47
Base, provision for alternative, in μ GT valves	63	Radiotrons, Australian-made, complete list of	50
Bases, rattle in	22	Radiotron Characteristics Chart	22
Bases, Valve, now made in Australia	50	Radiotron Characteristics Chart, availability of	30
Bass boost and attenuation	43	Radiotron Designer's Handbook, circulation 14,	22
Bias methods for preamplifiers	58	Radiotron Designer's Handbook, correction to	14
Book Review "Thermionic Tubes at very high frequencies" (A. F. Harvey)	47	Radiotron Equivalent Type Chart, shortage of	42
Book Review, "The Behaviour of Slow Electrons in Gases" (R. H. Healey and J. W. Reed)	19	Radiotron Equivalent Type Chart, Third Edition	56
Bypassing, cathode; derivation of formula	38	Radiotron Manuals RC14, TT3, TS2	38
Candlepower matching by phototube	7-9	Radiotron Receiving Type Manual RC14	14
Capacitance heater-cathode, values of	16	Radiotron Replacement Guide	42
Cathode bias with preamplifiers	58	Radiotronics binder covers	64
Cathode bypassing; derivation of formula	39	Radiotronics Subscriptions	42
Chassis for power supply, separate	21	Rattle in valve bases	22
Colour code for resistors, new R.M.A.	49	Recording Characteristics	62-63
Colour matching by phototube	7-9	Relays, light-operated	4, 6-7
Compensation for frequency drift	15-19	Resistors, new R.M.A. colour code	49
Converter considerations	23	Speech and music; relative energy distribution	37
Correction note, 5Y3-G data (Sept., 1940)	38	Sound reproduction by phototube	4
Coupling condensers, interstage	35	Temperature, effect on frequency of 6J5 oscillator	15-19
Data Sheet Handbook	38	Tone control, 4.5 watt amplifier with	51
Decoupling in preamplifiers	5-9	Tone compensation in audio amplifiers	43
Dielectric loss, measurement of, using Q meter	38	Treble boost and attenuation	43, 51
Exposure-control by phototube, photographic	9-10	Turbidity matching by phototube	7-9
Fixed bias with preamplifiers	58	Valve bases made in Australia	50
Frequency compensation in audio amplifiers	43	Volume control with preamplifiers, position of	58
Frequency of 6J5 oscillator, effect of tem- perature on	15-19	D63/6H6-G	14
Frequency stability in converters	25-26	Announcement	42
Grid bias for R.F. stages, operation with lower	47	Suspension of supplies	14
Grid circuit resistance of amplifier valves, maximum	38, 58	KT32/25L6-G	38
Grid circuit resistance of amplifier valves used with phototubes	5	Announcement	38
Grid leak bias with preamplifiers	58	Shortage of supply	38
GT valves, provision for alternative base	63	KT66/6L6-G	14
Hearing tests at World's Fair	21	Announcement	42
Heater-to-cathode capacitance, values of	16	L63/6J5-G	14
Hum in preamplifiers	59	Announcement	42
Illumination, measurement of very small values of	10	Suspension of supplies	14
Light; circuit for measurement of very small values of	10	N14/1C5G	14
Light intensity ratios, measurement of	8-9	Announcement	42
Light Measurements by phototube	4	Suspension of supplies	42
Light matching	7-9	U52/5U4G	14
Light-operated relays	4, 6	Announcement	42
Light-operated relay and measurements	6-7	Suspension of supplies	14
Magic-Eye Tuning Indicator for light matching	8	X64/6L7-G	42
Micromhos per milliamp	63	Announcement	42
Mixer and preamplifier considerations	57-61	Suspension of supplies as replacement for type 34	49
Music and speech; relative energy distri- bution	37	Announcement	22
Negative feedback amplifier; elimination of positive feedback at high audio fre- quencies	31-35	Announcement	38
Negative transconductance oscillator	48	Suspension of produc- tion, and replacement Maximum grid resistance	38
Noise, valve, in converters	23-26	1B7-GT	30
Oscillator, effect of temperature on frequency of 6J5	15-19	1C5-GT	22
Oscillator frequency stability in converters	25-26	1C5-GT/1C5-G	38
Oscillator, negative transconductance	48	1D5-GT	30
Photographic exposure control by phototube	9-10	1D8-GT	38
Phototubes	1-14	1G4-GT/1G4-G	38
		1G6-GT/1G6-G	38
		1H4-G	38
		1H5-GT	38
		1H6-G	38
		1J6-G	38
		1K4	38
		1K5-G	38
		1K6	38
		1K7-G	38
		1LA4	30
		1LA6	30

1LB4	Announcement	30	7E7	Announcement	22	
1LH4	Announcement	30	7F7	Announcement	22	
1LN5	Announcement	30	7G7/1232	Announcement	22	
1L5-G	Data Sheets, release of	22	7H7	Announcement	30	
1N5-GT	Maximum grid resistance	38	7J7	Announcement	22	
1P5-GT	Suspension of produc- tion and replacement for	49, 50	7Q7	Announcement	30	
	as replacement for		12A5	Announcement	30	
	1N5-GT	49	12B8-GT	Announcement	22	
1Q5-GT/1Q5-G	Announcement	38	12SA7-GT	Announcement	22	
2A4-G	Announcement	22	12SF5-GT	Announcement	30	
3Q5-GT/3Q5-G	Announcement	38	12SG7	Announcement	30	
3S4	Announcement	14	12SJ7-GT	Announcement	30	
5V4-G	Use of in 13 watt ampli- fier A504	31-35	12SK7-GT	Announcement	22	
	Temporary suspension of production	42	12SQ7-GT	Announcement	22	
	Recommencement of production	64	14A7/12B7	Announcement	30	
6A3	Announcement	22	25A6-GT	Announcement	30	
6AC5-GT	Announcement	22	25A7-GT	Announcement	30	
6AC5-GT/6AC5-G	Announcement	38	25B8-GT	Announcement	22	
6AD6-G	Announcement	22	25C6-G	Announcement	30	
6AE7-GT	Announcement	22	25Y5	Announcement	30	
6B4-G	Announcement	30	25Z6-GT/25Z6-G	Announcement	38	
6B6-G	Maximum grid circuit resistance	38	30	Maximum grid resistance	38	
	6B7	Maximum grid circuit resistance	38	32L7-GT	Announcement	22
	6B8-G	Increased ratings	20	34	Suspension of produc- tion, and repl. for ..	49, 50
		Maximum grid circuit resistance	38	35L6-GT/35L6-G	Announcement	38
		6C5-GT	Announcement	35Z5-GT/35Z5-G	Announcement	38
		6C6	Maximum grid circuit resistance	45	Additional data	64
			Used for light matching	50Y6-GT	Announcement	22
			Capacitance heater- cathode	50Z7-G	Announcement	30
			6E5	57	Maximum grid resistance	38
			6F6-G	75	Maximum grid resistance	38
				77	Maximum grid resistance	38
				83V	Recommencement of production	64
				85	Maximum grid resistance	38
					Suspension of produc- tion, and repl. for ..	42
				117L7-GT	Announcement	22
				117Z6-GT/117Z6-G	Announcement	38
				807	Australian-made, com- mercial release of	22
					Announcement	14
					Data	27-28
					Announcement	14
					Photograph	21
					Announcement	14
					Characteristics ..	1, 11-13
					Photograph and Char- acteristics ..	1, 11-13
					Characteristics ..	1, 11-13
					Characteristics ..	1, 11-13
					Application of ..	
					Characteristics ..	1, 11-13
					Photograph and char- acteristics ..	1, 11-13
					Characteristics ..	1, 11-13
					Characteristics ..	1, 11-13
					Photograph and char- acteristics ..	1, 2, 11-13
					Characteristics ..	1, 11-13
					Characteristics ..	1, 11-13
					Photograph and char- acteristics ..	1, 2, 11-13
					Photograph and char- acteristics ..	1, 11-13
					Photograph and char- acteristics ..	1, 11-13
					Announcement	30
					Data	29
					Availability and price	14
					Use of in preamplifier circuit	20, 57-61
					Maximum grid resistance	38
					Announcement	14
					Announcement	14
					Announcement	22
					Announcement	30
					Announcement	30
					Announcement	30
					Use in phototube circuit	5
					Use in phototube circuit	4, 6
					Announcement	22
					Data	36
6J7-G	Capacitance heater- cathode	16	815	Announcement	14	
	Use of in preamplifiers	57-61	826	Data	27-28	
	Increased ratings ..	20	829	Announcement	14	
	Use of in 13 watt ampli- fier A504	31-35	866A/866	Photograph	21	
	Maximum grid circuit resistance	38	868	Announcement	14	
	Alterations to charac- teristics	50	917	Characteristics ..	1, 11-13	
	Suspension of produc- tion, and replacement	56	918	Photograph and Char- acteristics ..	1, 11-13	
	Suspension of produc- tion, and replacement	56	919	Characteristics ..	1, 11-13	
	Announcement	22	920	Characteristics ..	1, 11-13	
	May be replaced by 807	22	921	Application of ..		
	Announcement	22	922	Characteristics ..	1, 11-13	
	Announcement	22	923	Photograph and char- acteristics ..	1, 2, 11-13	
	Announcement	22	924	Characteristics ..	1, 11-13	
	Announcement	22	925	Characteristics ..	1, 11-13	
	Announcement	30	926	Characteristics ..	1, 11-13	
	Announcement	30	927	Photograph and char- acteristics ..	1, 2, 11-13	
	Announcement	30	928	Photograph and char- acteristics ..	1, 11-13	
	Announcement	22	929	Photograph and char- acteristics ..	1, 11-13	
	Announcement	22	930	Announcement	30	
	Increase of plate and screen dissipation ..	50	1603	Data	29	
	Increased screen voltage	56	1625	Availability and price	14	
	Use of in 13 watt ampli- fier A504	31-35	1626	Use of in preamplifier circuit	20, 57-61	
	Capacitance heater- cathode	16	1629	Maximum grid resistance	38	
	Announcement	30	1631	Announcement	14	
	Australian-made, release	22	1632	Announcement	14	
	Availability of	30	1633	Announcement	22	
	Announcement	38	2050	Announcement	30	
	Temporarily not avail- able	42	2051	Announcement	30	
	Announcement	22	8000	Announcement	30	
	Announcement	22	8003	Use in phototube circuit	5	
	Announcement	22		Use in phototube circuit	4, 6	
	Announcement	30		Announcement	22	
	Announcement	22		Data	36	
7A4	Announcement	22				
7A5	Announcement	22				
7B4	Announcement	30				
7E6	Announcement	22				