

AMENDMENT NO. 1.

Page 2

Group "g"

Amend frequency
figure from 9320 Mc/s
to 8770 Mc/s

February, 1959.
N.54384/D.

Admiralty Signal & Radar Establishment

SPECIFICATION AD/CV2262
ISSUE NO. 5 DATED 24.10.58

AMENDMENT NO. 2

Insert new Pages 6 and 7 attached.

Endorse existing Page 4 "Cancelled - see Page 6".
" existing Page 5 "Cancelled - see Page 7".

Page 1 Top left-hand corner

Amend No. of pages from "5" to "7".

November, 1960

T.V.C. for A.S.W.E.

N.34357

ELECTRONIC VALVE SPECIFICATIONS

SPECIFICATION AD/CV2262

ISSUE NO. 5 DATED 24.10.58.

AMENDMENT NO. 3

Page 3 2(iii) 1st line

Amend $\frac{V}{CR}$ to $\frac{V 10^{-3}}{CR}$

2(iii) 3rd line

Amend "(Fds)" to " μ Fds)"

January, 1961
NC 47054

ADMIRALTY SURFACE WEAPONS ESTABLISHMENT

VALVE ELECTRONIC

ADMIRALTY SIGNAL AND RADAR ESTABLISHMENT

CV2262

Specification AD/CV2262. Issue No. 5 dated 24.10.58. To be read in conjunction with K1001	<u>SECURITY</u> Specification Valve Unclassified Unclassified
---	---

← Indicates a change

<p><u>TYPE OF VALVE:</u> Magnetron, X-Band, packaged, pulsed, tunable.</p> <p><u>CATHODE:</u> Indirectly heated; oxide-coated.</p> <p><u>ENVELOPE:</u> Metal-glass.</p> <p><u>PROTOTYPE:</u> V14129</p>	<u>MARKING</u> See K1001/4 Additional marking: Serial No. See also Note 'E'
--	--

<u>RATINGS</u>	<u>Note</u>	<u>DIMENSIONS AND CONNECTIONS</u>
Heater Voltage (V) 5.5	A	See drawing on pages 4 & 5.
Heater Current (A) 1.37		
Nominal Frequency Range (Mc/s) 8500 to 9050		
Max. Mean Input Power (W) 150	B	
Max. Frequency Pulling Figure (Mc/s) 15	C	
<u>TYPICAL OPERATING CONDITIONS</u>		D
Peak Anode Voltage (kV) 14		
Peak Anode Current (A) 14		
Peak Output Power (kW) 60		

NOTES

- A. The heater supply should be switched on for at least 3 minutes before H.T. is applied. Full heater power is required for starting only; during oscillation heater voltage should be reduced to $V_h = 5.5 (1 - 0.007 P_m)$ where P_m is mean input power in Watts.
- B. When operating, the magnetron must be air-cooled so that the temperature of the block surface does not exceed 140°C.
- C. See test (e).
- D. These operating conditions apply for a pulse duration of 0.1 μs and a pulse repetition rate of 3000 pps. The rate of rise of the voltage pulse must not exceed 140 kV/μsec. (Measured as described in the Appendix, Page 3).
- E. No technical information shall appear on the valve or packing.

TESTS

To be performed in addition to those applicable in K1001, and after a holding period of at least 28 days.

	Test Conditions		Test	Limits		No. Tested	Note
	V _h (V)	Mean I _a (mA)		Min.	Max.		
a	5.5	-	I _h (A)	1.25	1.50	100%	
b	See Note 1	4	Lowest Operating Frequency (Mc/s)	-	8500	100%	2,3.
			Highest Operating Frequency (Mc/s)	9035	9050	100%	
Tests (c), (d), (e) and (f) shall be carried out at each of the following nominal frequencies:- 8500 Mc/s, 8660 Mc/s, 8800 Mc/s, 8920 Mc/s and 9050 Mc/s.							
c	See Note 1	4	Peak V _a (kV)	11	15.5	100%	2,3.
d	See Note 1	4	Mean Power Output (W)	15 ±	-	100%	2,3,6.
e	See Note 1	4	Frequency Pulling (Mc/s)	-	15	100%	2,4.
f	See Note 1	4	Moding (%)	-	1.0	100%	2,4,5.
g	See Note 1	4	I _{afe} at 9320 Mc/s (Hrs.)	500	-	1 in 30	2,3,7.

NOTES

- The valve shall be run for a period of not more than 3 mins. with V_h = 5.5 volts. At the end of that time the H.T. voltage shall be switched on and the heater voltage simultaneously reduced to the value specified in Note A. This heater voltage shall apply to all the tests except test (a).
- The magnetron shall be tested in equipment which has been approved by the specifying authority. The pulse characteristics being:-
 $t_p = 0.1 \mu s.$ P.R.F. = 3000 pps.
 $r.r.v. = 14 kV/\mu sec$ (min). Measured as described in the Appendix - page 3.
- The waveguide system shall be terminated in a resistive load giving a V.S.W.R. not greater than 1.1:1.
- A mismatch producing a V.S.W.R. of 1.5 shall be moved through a distance of half a guide-wavelength. Continuous observation of the frequency spectra shall be made during this operation. Valves showing spectra with side lobes of power greater than 1/10 of that of the central lobe shall be rejected.
- If the moding figures obtained at the five specified frequencies are all in excess of 0.7%, further moding figures shall be determined at four intermediate frequencies. The apparatus used to measure the moding is to be checked for accuracy before each valve is measured. Details of an arrangement for measuring the moding may be obtained from the Specifying Authority.
- The apparatus used for power measurement shall be checked after every 100 valves tested, or once per month (whichever the shorter period) against a calorimetric method of measurement.
- The life of a valve shall be considered to be terminated if its performance falls outside the limits of any one of the tests b-f. If the valve selected for life test passes the test, the lot shall be accepted. However, if this valve fails to pass the test, another valve from the same lot shall be life tested. If this second valve passes the test the lot shall be accepted; but if this valve also fails to pass the test, the lot shall be rejected. A rejected lot may be re-submitted for acceptance following a joint investigation by the contractor and the government authority concerned.



