

VALVE ELECTRONIC CV2398.

ADMIRALTY SIGNAL AND RADAR ESTABLISHMENT

Specification AD/CV2398 Issue No. 1 dated 4.12.56. To be read in conjunction with K1001 ignoring Clause 5.8, and B.S.1409	<u>SECURITY</u>	
	<u>Specification</u>	<u>Valve</u>
	Unclassified	Unclassified

<u>TYPE OF VALVE:</u> Noise Diode for frequencies up to 500 Mc/s. <u>CATHODE:</u> Directly Heated, Tungsten. <u>ENVELOPE:</u> Glass. <u>PROTOTYPE:</u> VX3518.	<u>MARKING</u>		
	See K1001/4		
	<u>BASE</u>		
	B9a/F		
<u>RATINGS</u>		<u>CONNECTIONS</u>	
All limiting values are absolute.		Lead	Electrode
	Notes		
Max. Filament Voltage (V)	6.0 A	1	a
Filament Current (nom.) at Vf = 6V. (A)	1.15	2	IC
Min. Saturated Anode Current at Vf = 5.6V. (mA)	45 B	3	a
Max. Anode Voltage (V)	200	4	f
Max. Anode Dissipation (W)	3.5	5	f
		6	a
		7	IC
		8	a
		9	IC
<u>CAPACITANCE (pF)</u>		<u>DIMENSIONS</u>	
ca. f (max.)	3.0	See K1001/A.1/D.11	
		Dimension (mm)	Min. Max.
		A	- 49.0
		B	19.0 22.2
		D	35.0 -
<u>NOTES</u>			
A. The value of the saturated Ia is determined by the value of Vf. At the max. Vf of 6V the life of the filament is only about 25 hours.			
B. The design of the valve is such that a saturated anode current of at least 45 mA is obtained at Va = 50V.			

TESTS

CV2398. To be performed in addition to those applicable in K1001.

	Test Conditions			Test	Limits		No. Tested	Note
					Min.	Max.		
a	Links to HP	Links to LP	Links to F	<u>CAPACITANCE</u> Ca, f (pF)	-	3.0	6 per week.	
	1,3,6,8	4,5	2,7,9,10 TC1,TC2					
b	Vf (V)	Va (V)		If (A)	1.08	1.22	100%	
	6.0	0						
c	6.0	25		Ia (mA)	38	-	100%	
d	6.0	50		Ia (mA)	60	-	100%	
e	5.6	50		Ia (mA)	45	55	100%	

CV2398/1/2