

Specification MOSA/CV3798 Issue 2 Dated 26.11.1952 To be read in conjunction with K.1001	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

—→ Indicates a change

TYPE OF VALVE - Voltage Stabiliser  CATHODE - Cold  ENVELOPE - Glass, unmetallised  PROTOTYPE - OA3/VR75/30		<u>MARKING</u> See K.1001/4																			
		<u>BASE</u> I.O See K1001/AIV/D2																			
<u>RATING</u>		Note	<u>CONNECTIONS</u>																		
Max. Striking Voltage (V) 105 Operating Voltage (Approx.) (V) 75 Min. Operating Current (mA) 5 Max. Operating Current (mA) 40			<table border="1"> <thead> <tr> <th>Pin</th> <th>Electrode</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>No connection</td> </tr> <tr> <td>2</td> <td>Cathode</td> </tr> <tr> <td>3</td> <td>Connected internally to pin 7</td> </tr> <tr> <td>4</td> <td>Pin omitted</td> </tr> <tr> <td>5</td> <td>Anode</td> </tr> <tr> <td>6</td> <td>Pin omitted</td> </tr> <tr> <td>7</td> <td>Connected internally to pin 3</td> </tr> <tr> <td>8</td> <td>No connection</td> </tr> </tbody> </table>	Pin	Electrode	1	No connection	2	Cathode	3	Connected internally to pin 7	4	Pin omitted	5	Anode	6	Pin omitted	7	Connected internally to pin 3	8	No connection
Pin	Electrode																				
1	No connection																				
2	Cathode																				
3	Connected internally to pin 7																				
4	Pin omitted																				
5	Anode																				
6	Pin omitted																				
7	Connected internally to pin 3																				
8	No connection																				
		<u>DIMENSIONS</u> See K.1001/A1/D1																			
		Dimensions	Min.      Max.																		
		A mm	96      105																		
		B mm	-      40																		

Test Conditions			Test	Limits		No. Tested	Note
				Min.	Max.		
a	Va(V)	Ia (mA)	Striking Voltage(V)	-	105	100%	1 & 2
	Increased from zero until Ia flows.						
b	Adjusted	40	Va (V)	-	81	100%	2
c	Adjusted	30	Va (V)	-	79	100%	2
d	Adjusted	5	Va (V)	70	-	100%	2
e	50	-	Leakage Current( $\mu$ A)	-	10.0	1%(5)	2
f	<u>Impedance</u>			(V)	-	6.5	100%
	(i) Difference between value of Va in test "b" and value in test "d".						
	(ii) Difference between value of Va in test "c" and value in test "d".			(V)	-	4.5	1%(5)
g	<u>Noise Test</u>		<p>The valve is to be tested for freedom from oscillation and noise during operation. For this purpose a calibrated amplifier detector having a level response within <math>\pm</math> 2db. of its response at 400 c.p.s. over the range of 50-5000 c.p.s. is to be connected between the Anode and Cathode. The cathode current is to be varied slowly from 5mA to 40mA and at no point in this range must the R.M.S. noise input voltage to the amplifier exceed 5mV. For the purpose of the test the valve shall be operated from a well filtered variable D.C. supply</p>				
						100%	
<u>NOTES</u>							
1. This test is to be performed 24 hours after the valve is sealed off.							
2. With a minimum resistance of 1K ohms in series with the anode.							