

VALVE ELECTRONICADMIRALTY SURFACE WEAPONS ESTABLISHMENT

Specification AD/CV.4048 Issue No. 2, Reprint A dated 1st December, 1962. To be read in conjunction with K1001 excluding clauses 5.2 and 5.8, BS448 and BS1409		<u>SECURITY</u>	
		<u>Specification</u>	<u>Valve</u>
		Unclassified	Unclassified
→ Indicates a change			
<u>TYPE OF VALVE:</u>	Reliable, Gas-filled Voltage Reference Tube	<u>MARKING</u>	
<u>CATHODE:</u>	Cold	See K1001/4	
<u>ENVELOPE:</u>	Glass	<u>BASE</u>	
<u>PROTOTYPE:</u>	VX8098	See BS448/B7G	
<u>EQUIVALENT FLYING LEAD VALVE:</u>	CV4054		
<u>RATINGS</u>		<u>CONNECTIONS</u>	
(All limiting values are absolute)			
		Note	Pin
			Electrode
→ Min. Supply Voltage (V)	115	A	1 Anode a
Recommended Operating Current (mA)	6.0		2 cathode k
Max. Cathode Current (mA)	10		3 internally connected ic
→ Min. Cathode Current (mA)	1.0		4 cathode k
→ Max. Starting Current (mA)	4.0	B	5 anode a
Max. Acceleration (g)	2.5		6 internally connected ic
→ Max. Shock (short duration) (g)	500	C	7 cathode k
→ Max. Operating Bulb Temp. (°C)	90	D	
→ Max. Ambient Storage Temp. (°C)	70		
Min. Ambient Temperature (°C)	-55		
<u>CHARACTERISTICS</u>		E	<u>DIMENSIONS</u>
Nominal Maintaining Voltage (V)	85		See BS448/B7G/2.1 Size Ref. No. 2
Max. Incremental Resistance (ohms)	450		
→ Nominal Incremental Resistance (ohms)	350		Dimensions (mm)
→ Max. Regulation Voltage (V)	4		Min. Max.
(1-10 mA)			A seater height - 47.5
→ Max. Jump Voltage (1-10 mA) (mVpk)	100		F C diameter 16.0 19.0
→ Typical Random Noise Voltage (30 o/s to 10 Kc/s) (μVrms)	75		D overall length - 54.5
Nominal Temperature Co-efficient			<u>MOUNTING POSITION</u>
(a) -55°C to +25°C (mV/°C)	-7		Any
(b) +25°C to +90°C (mV/°C)	-3		
Max. Percentage Drift of Maintaining Voltage			
(a) 0-300 hours (%)	0.3	G	
(b) 300-1300 " (%)	0.2	G	
Typical Percentage Drift of Maintaining Voltage per 1000 hours after 1300 hours (%)	0.1	G	
Min. Life Expectancy (hours)	10,000		

NOTES

- A. This figure is applicable in ambient light or total darkness at room temperature, during the life of the valve. In total darkness an ignition delay of up to approximately 5 seconds may occur. ←
- B. This is to be restricted to 60 seconds once or twice in every 8 hours use if the stability is to be maintained. ←
- C. For greater reliability the operating bulb temperature should be maintained as constant as possible and the higher temperatures should be avoided. If the tube is to be operated with a bulb temperature above 70°C the cathode current should be not less than 6.0mA. ←
- D. In order to retain the best reference stability during prolonged storage the ambient temperature should be kept as near to room temperature as possible and the limit rating must never be exceeded. ←
- E. These are all measured at $I_c=6mA$ and normal room temperature unless otherwise stated.
- F. This is a random variation of the maintaining voltage, which is generated solely within the valve, due to the discrete nature of the ion current. The energy is uniformly distributed over the frequency spectrum. ←
- G. After an initial warming-up period of 3 minutes.
- H. Caution to Electronic Equipment Design Engineers
Special attention should be given to the temperature of valves to be operated in service equipment. Reliability will be seriously impaired if the maximum bulb temperature is exceeded. The life expectancy may be reduced if conditions other than those specified for life tests are imposed on the valve and will be reduced appreciably if absolute maximum ratings are exceeded. ←

TESTS

To be performed in addition to those applicable in K1001.

Tests are to be performed in the specified order unless other-wise agreed with the Inspecting Authority.

Test Conditions - Unless Otherwise Stated								
Rlim (Kohms) 5 to 20		Ik(mA) 6						
K1001 Ref	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits		Units
						Min.	Max.	
<u>Group A</u>								
5G13	Leakage Current	V Supply = 55V Rlim = 1Mohm						
	Pin Continuity			100%		-	5	uA
5G1.1	Striking Time (1)	Va = 115V		100%	ts	-	5	secs.
<u>Group B</u>								
5G3	Maintaining Voltage	Note 1	0.65	II	Vm	83	87	V
5G4	Regulation (1)	Ik=5.8mA, Ik=6.2mA	0.65	II	ΔVm	-	0.18	V
5G7	Voltage Jumps	Ik varied between 10mA and 1.0mA Note 2	0.65	II		-	100	Mvpk
5G8	Microphonic Noise	Note 3	0.65	II		-	15	mV pk-pk
<u>Group C</u>								
5G1.1 } 5G2 }	Striking Time (2)	Va=115V Note 4	2.5	I	ts	-	5	secs.
5G4	Regulation (2)	Ik=1.0mA Ik=10mA	2.5	I	ΔVm	-	4	V
<u>Group D</u>								
5G10	Temp. Coefficient (1)	T. Bulb -55°C & +25°C			T.A.	-	12	-mV/°C
5G10	Temp. Coefficient (2)	T. Bulb 25°C & +90°C			T.A.	-	5	-mV/°C
5G1.2	Striking Voltage (1)	T. Bulb -55°C			T.A.	Vs	120	V
5G1.2	Striking Voltage (2)	T. Bulb +90°C			T.A.	Vs	115	V
5G4	Regulation (3)	Ik=1.0mA Ik=10mA T. Bulb = +90°C			T.A.	ΔVm	4	V
5G4	Regulation (4)	Ik=1.0mA Ik=10mA T. Bulb = -55°C			T.A.	ΔVm	5	V
5G6	Oscillation	Ik varied between 10mA and 1mA Time of sweep 5 ⁺² sec. Note 5			T.A.		5	mV pk. pk

TESTS (Cont'd.)

K1001 Ref	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits		Units
						Min.	Max.	
	<u>Group E</u>							
AIX/ 2.4.2.1.	Glass Strain	No Voltages	6.5	I				
AIX/ 2.4.2.2	Base Strain	No Voltages	6.5	IA				
5G9	Resonance Search (1)	Rlim = 27kohms						
AIX/ 2.4.2.4.1		Freq.25-500c/s	2.5	IA		-	15	mV pk-pk
5G9	Resonance Search (2)	Rlim = 27kohms						
AIX/ 2.4.2.1		Freq.500-2500"	2.5	IA		-	45	mV pk-pk
AIX/ 2.4.2.4.2	Fatigue	No Voltages Duration 30 + 30 + 39 hours Accln = 5g Freq. = 170c/s		IA				
	<u>Post Fatigue Tests</u>	Combined AQL Note 6	4.0					
5G3	Change in Main- taining Voltage	Notes 1 and 7	2.5		Δ Vm	-	±0.7	V
5G8	Microphonic Noise	Note 3	2.5			-	30	mV pk-pk
AIX/ 2.4.2.4.3	Shock	No Voltages Hammer Angle 30°		IA				
	<u>Post Shock Tests</u>	Combined AQL Note 6	4.0					
5G3	Change in Main- taining Voltage	Notes 1 and 7	2.5		Δ Vm	-	±0.7	V
5G8	Microphonic Noise	Note 3	2.5			-	30	mV pk-pk
	<u>Group F</u>							
AIX/ 2.4.3	Life Test	Note 8		IA				
	<u>End Point Tests</u>							
	1000 hours	Note 6						
5.14	Inoperatives		2.5					
5G1.1	Striking Time (1)	Va = 115V	2.5		ts	-	5	secs.
5G3	Change in Main- taining Voltage	Notes 1 & 7	2.5		Δ Vm	-	0.4	V
5G4	Regulation (1)	IK = 5.8mA IK = 6.2mA	2.5		Δ Vm	-	0.18	V

TESTS (Cont'd.)

K1001 Ref	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits		Units
						Min.	Max.	
	<u>Group G</u>							
AIX/ 2.5	Electrical Retest after 28 days Holding Period			100%				
5.14	Inoperatives		0.5					
5G1.1	Striking Time (1)	Va = 115V	0.5		ts	-	5	secs. ←
5G3	Maintaining Volt	Note 1			Vm	83	87	V
5G4	Regulation (1)	I _k =5.8mA I _k =6.2mA			Δ Vm	-	0.18	V

NOTES

1. After the valve has ignited, (in the striking time or striking voltage tests) it shall be operated at I_k=6mA for 3 minutes before any other characteristic is measured. ←
2. The time of sweep shall be 5±2 seconds. The sweep may be made with either increasing or decreasing current. ←
3. The valve shall be tapped 3 times in each of two mutually perpendicular lateral directions using an approved device and the noise shall not exceed the specified limit. ←
4. This test is to be conducted in total darkness after the valve has been held inoperative in total darkness for at least 24 hours.
5. Any oscillation which persists over a current range of less than 1.0mA shall be considered as a voltage jump. ←
6. Where a valve fails more than one end point test, that test occurring first in the list of end point tests shall be deemed to be the cause of failure. ←
7. This is the change in maintaining voltage from the initial value. ←
8. This life test shall be run continuously for the specified period. A Stability Life Test is not required. ←