

Half-Wave Vacuum Rectifier

DUODECAR TYPE

Electrical:

Heater Characteristics and Ratings:

Voltage (AC or DC)	6.3 ± 0.6	volts
Current at heater volts = 6.3	1.200	amp

Peak heater-cathode voltage:

Heater negative with respect to cathode^a 5000^b max. volts

Heater positive with respect to cathode 300^c max. volts

Direct Interelectrode Capacitances (Approx.):^d

P to (K,H)	10	pf
K to (P,H)	8.0	pf
H to K	3.4	pf

Mechanical:

Operating Position	Any
Type of Cathode	Coated Unipotential
Maximum Overall Length	2.875"
Seated Length	2.250" to 2.500"
Diameter	1.062" to 1.188"
Dimensional Outline	See General Section
Bulb	T9
Base	Small-Button Duodecar 12-Pin (JEDEC No.E12-70)
Basing Designation for BOTTOM VIEW	12BL

Pin 1 - Heater

Pin 2 - No Internal Connection

Pin 3 - Same as Pin 2

Pin 4 - Plate

Pin 5 - Same as Pin 2

Pin 6 - Same as Pin 2

Pin 7 - Cathode


Pin 8 - Same as Pin 2

Pin 9 - Same as Pin 2

Pin 10 - Plate

Pin 11 - Same as Pin 2

Pin 12 - Heater



DAMPER SERVICE

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^e

Peak Inverse Plate Voltage ^a	5000	max.	volts
Peak Plate Current	1200	max.	ma
DC Plate Current	200	max.	ma
Plate Dissipation	6.5	max.	watts

Characteristics, Instantaneous Value:

Tube Voltage Drop for plate ma. = 350	25	volts
---	----	-------



6BE3

- a This rating is applicable when the duration of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.
- b The dc component must not exceed 900 volts.
- c The dc component must not exceed 100 volts.
- d Without external shield.
- e As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

