

Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

GENERAL DATA

Electrical:

Heater Characteristics and Ratings (*Design-Center Values*):

Voltage (AC or DC)	6.3 ± 0.6	volts
Current at heater volts = 6.3	0.300	amp
Peak heater-cathode voltage:		
Heater negative with respect to cathode	150 max.	volts
Heater positive with respect to cathode	150 max.	volts

Direct Interelectrode Capacitances:^a

Grid No.1 to plate	0.005 max.	μf
Grid No.1 to cathode, grid No.3, grid No.2, internal shield, and heater	10	μf
Plate to cathode, grid No.3, grid No.2, internal shield, and heater	3	μf


Characteristics, Class A₁ Amplifier:

Plate Voltage	190	200	volts
Grid No.3	<i>Connected to cathode at socket</i>		
Grid-No.2 Voltage	190	200	volts
Grid-No.1 Voltage	-2.35	-2.5	volts
Plate Resistance (Approx.)	0.35	0.35	megohm
Transconductance	15000	15000	μmhos
Plate Current	10	10	ma
Grid-No.2 Current	4.1	4.1	ma

Mechanical:

Operating Position	Any
Type of Cathode	Coated Unipotential
Maximum Overall Length	2-13/32"
Maximum Seated Length	2-5/32"
Length, Base Seat to Bulb Top (Excluding tip)	1-25/32" ± 3/32"
Diameter	0.750" to 0.875"
Bulb	T6-1/2
Base	Small-Button Noval 9-Pin (JEDEC No.E9-1)
Basing Designation for BOTTOM VIEW	9AQ

- Pin 1 - Cathode
- Pin 2 - Grid No.1
- Pin 3 - Cathode
- Pin 4 - Heater
- Pin 5 - Heater



- Pin 6 - Internal Shield
- Pin 7 - Plate
- Pin 8 - Grid No.2
- Pin 9 - Grid No.3



6EJ7

AMPLIFIER — Class A₁

Maximum Ratings, Design-Center Values:

PLATE SUPPLY VOLTAGE	550 max.	volts
PLATE VOLTAGE	250 max.	volts
GRID No.3 (SUPPRESSOR GRID)	<i>Connect to cathode at socket</i>	
GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE.	550 max.	volts
GRID-No.2 VOLTAGE	250 max.	volts
CATHODE CURRENT	25 max.	ma
GRID-No.2 INPUT	0.9 max.	watt
PLATE DISSIPATION	2.5 max.	watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance.	1 max.	megohm
---------------------------------------	--------	--------

^a without external shield.

