



6W6-GT

6W6-GT

BEAM POWER AMPLIFIER

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage	6.3	ac or dc volts
Current	1.2	amp
Direct Interelectrode Capacitances (Approx.):		
Grid No.1 to Plate	0.5 max.	μuf
Input	15	μuf
Output	9	μuf

Characteristics as Beam Power Amplifier:

See AMPLIFIER—Class A₁ below:

Characteristics as Triode-Connected Amplifier:

(Grid No.2 connected to plate)


Plate Voltage	225	volts
Grid-No.1 Voltage	-30	volts
Amplification Factor	6.2	
Plate Resistance	1600	ohms
Transconductance	3800	μmhos
Plate Current	22	ma
Grid-No.1 Voltage (Approx.) for plate current of 0.5 ma	-42	volts

Mechanical:

Mounting Position	Any
Maximum Overall Length	3-5/16"
Maximum Seated Length	2-3/4"
Maximum Diameter	1-9/32"
Bulb	T-9
Base.	Intermediate-Shell Octal 6-Pin (JETEC No.86-8) or Intermediate-Shell Octal 7-Pin (JETEC No.87-7) or Short Intermediate-Shell Octal 6-Pin with Ex- ternal Barriers (JETEC No.86-80) or Short Intermediate-Shell Octal 7-Pin with Ex- ternal Barriers (JETEC No.87-59) ←

Basing Designation for BOTTOM VIEW G-7AC

Pin 1—No	Connection
Pin 2—Heater	
Pin 3—Plate	
Pin 4—Grid No.2	



Pin 5—Grid No.1
Pin 7—Heater
Pin 8—Cathode, Grid No.3

AMPLIFIER—Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE	300 max.	volts
GRID-No.2 (SCREEN) VOLTAGE	150 max.	volts
PLATE DISSIPATION	10 max.	watts
GRID-No.2 INPUT	1.25 max.	watts

← Indicates a change.

6W6-GT



6W6-GT

BEAM POWER AMPLIFIER

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode	200 max.	volts
Heater positive with respect to cathode	200 [▲] max.	volts

Typical Operation and Characteristics:

Plate Supply Voltage.	110	200	volts
Grid-No.2 Voltage	110	125	volts
Grid-No.1 (Control-Grid) Voltage	-7.5	-	volts
Cathode-Bias Resistor	-	180	ohms
Peak AF Grid-No.1 Voltage	7.5	8.5	volts
Zero-Signal Plate Current	49	46	ma
Max.-Signal Plate Current	50	47	ma
Zero-Signal Grid-No.2 Current	4	2.2	ma
Max.-Signal Grid-No.2 Current	10	8.5	ma
Plate Resistance (Approx.)	13000	28000	ohms
Transconductance	8000	8000	μ hos
Load Resistance	2000	4000	ohms
Total Harmonic Distortion (Approx.)	10	10	%
Max.-Signal Power Output	2.1	3.8	watts

Maximum Circuit Values:**Grid-No.1-Circuit Resistance:**

For fixed-bias operation	0.1 max.	megohm
For cathode-bias operation	0.5 max.	megohm

VERTICAL DEFLECTION AMPLIFIER*Triode Connected--Grid No.2 Connected to Plate***Maximum Ratings, Design-Center Values Except As Noted:***For operation in a 525-line, 30-frame system*

DC PLATE VOLTAGE	300 max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE [▲]	1200 [▲] max.	volts
PEAK NEGATIVE-PULSE GRID-No.1 (CONTROL-GRID) VOLTAGE	-250 max.	volts
CATHODE CURRENT:		
Peak	140 max.	ma
DC	40 max.	ma
PLATE DISSIPATION	7.5 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode	200 max.	volts
Heater positive with respect to cathode	200 [▲] max.	volts

Maximum Circuit Values:**Grid-No.1-Circuit Resistance:**

For cathode-bias operation	2.2 max.	megohms
--------------------------------------	----------	---------

[▲] The dc component must not exceed 100 volts.

● As described in "Standards of Good Engineering Practice for Television Broadcast Stations", Federal Communications Commission.


○ The duration of the voltage pulse must not exceed 15 per cent of one scanning cycle. In a 525-line, 30-frame system, 15 per cent of one scanning cycle is 2.5 milliseconds.

● Under no circumstances should this absolute value be exceeded.



6W6-GT

6W6-GT

AVERAGE PLATE CHARACTERISTICS
PENTODE CONNECTIONE_f = 6.3 VOLTS
GRID-N^o2 VOLTS = 125

MAR. 20. 1953


TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-7942

6W6-GT



6W6-GT
AVERAGE PLATE CHARACTERISTICS
TRIODE CONNECTION



MAR. 11, 1953

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-7943