

Test Picture Tube**NO ION-TRAP MAGNET REQUIRED****RECTANGULAR GLASS TYPE
ELECTROSTATIC SELF FOCUS****ALUMINIZED SCREEN
110° MAGNETIC DEFLECTION****Electrical:**

Direct Interelectrode Capacitances:

Cathode to all other electrodes.	4	pf
Grid No.1 to all other electrodes.	6	pf
Heater Current at 6.3 volts.	600	ma
Electron Gun	Type Requiring No Ion-Trap Magnet	

Optical:

Phosphor (For curves, see front of this section) . . . P4—Sulfide Type,		
		Aluminized
Faceplate.		Filterglass
Light transmission (Approx.)		80%


Mechanical:

Weight (Approx.)	2 lbs
Overall Length	8.69" ± .31"
Neck Length.	5.19" ± .19"
Projected Area of Screen	39 sq. in.
External Conductive Coating.	None

For Additional Information on Dimensions:

See *Picture-Tube Dimensional-Outlines and Bulb J67-1/2 B*
sheets at front of this sectionCap. Recessed Small Cavity (JEDEC No.J1-21)
Bases (Alternates):

Special 6-Pin (JEDEC No.B6-185)	
Special 6-Pin (JEDEC No.B6-214)	
Basing Designation for BOTTOM VIEW	7FG
Pin 2-Cathode	
Pin 3-Heater	
Pin 4-Heater	
Pin 5-Grid No.1	
Pin 6-No Internal Connection	
Pin 7-Grid No.2, Grid No.4	
Cap-Anode	
(Grid No.3, Grid No.5, Screen, Collector)	

**Maximum Ratings, Design-Maximum Values:**Unless otherwise specified, voltage values
are positive with respect to cathode

Anode Voltage.	22000	volts
Grid-No.2 and Grid-No.4 Voltage.	550	volts
Grid-No.1 Voltage:		
Negative peak value.	220	volts
Negative bias value.	155	volts
Positive bias value.	0	volts
Positive peak value.	2	volts

RADIO CORPORATION OF AMERICA
Electronic Components and Devices

Harrison, N. J.

DATA
4-65

Peak Heater-Cathode Voltage:

Heater negative with

respect to cathode:

During equipment warm-up period

not exceeding 15 seconds 450 volts

After equipment-warm-up period 200 volts

Heater positive with respect to cathode 200 volts

Typical Operating Conditions for Cathode-Drive Service:

*Unless otherwise specified, voltage values
are positive with respect to Grid No. 1*

Anode Voltage. 16000 volts

Grid-No.2 and Grid-No.4 Voltage. 400 volts

Cathode Voltage for visual extinction

of focused raster. 42 to 78 volts

Maximum Circuit Value:

Grid-No.1-Circuit Resistance 1.5 megohms

For X-radiation shielding considerations, see sheet

*X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this Section*

