

EDISWAN

DLS24

VACUUM THERMAL DELAY SWITCH

REVERSE ACTION

GENERAL

The DLS24 is a Miniature based Reverse Action Vacuum Thermal Delay Switch having AC switch ratings of 1 amp at 240 volts or 200 mA at 500 volts. It has a heater rating of 0.5 amps at 6.3 volts and a switch opening delay time of from 30 to 90 seconds, the switch being closed when cold. It is compensated to maintain a constant opening delay time in the ambient temperature range -40°C to $+85^{\circ}\text{C}$.

RATING

Heater Voltage (volts)	V_h	6.3
Heater Current (amps)	I_h	0.5
Minimum Delay Time (secs)	$t_{sd}(\text{min})$	30
Maximum Delay Time (secs)	$t_{sd}(\text{max})$	90
Maximum Switch Current at 240 volts (r.m.s.) (AC) (amps)	$I(\text{r.m.s.}) \text{ max}$	1.0
Maximum Switch Current at 500 volts (r.m.s.) (AC) (mA)	$I(\text{r.m.s.}) \text{ max}$	200
Maximum Heater to Contact Voltage (volts)	V_{h-c}	200
Heater Resistance (cold) (ohms)	$r_h (\text{min})$	1.3

DIMENSIONS

Maximum Overall Length	(mm)	54
Maximum Seated Height	(mm)	48
Maximum Diameter	(mm)	19
Approximate Nett Weight	(ozs)	$\frac{1}{4}$
Approximate Packed Weight	(ozs)	$\frac{1}{2}$

MOUNTING POSITION—Unrestricted

OPERATION

See 'Application notes on Vacuum Thermal Delay Switches.'


DLS24

EDISWAN

DLS24

VACUUM THERMAL DELAY SWITCH REVERSE ACTION

BASE—B7G



Viewed from free end of pins

VALVE HOLDER—Ediswan Clix VH337/702 and VH437/702 series.

CONNECTIONS

Pin 1	Heater	h
Pin 2	No Connection	NC
Pin 3	Moving Contact	cm
Pin 4	Fixed Contact	cf
Pin 5	No Connection	NC
Pin 6	No Connection	NC
Pin 7	Heater	h

May 1960

Issue 1/7

RADIO & ELECTRONIC COMPONENTS DIVISION

ASSOCIATED ELECTRICAL INDUSTRIES LTD.