


## TUNG-SOL




## BEAM POWER AMPLIFIER

## UNIPOTENTIAL CATHODE

HEATER  
35 VOLTS 0.15 AMPERE  
AC OR DC

## GLASS BULB

7AC  
BOTTOM VIEW

## 7 PIN OCTAL BASE

THE TUNG-SOL 35L6GT IS DESIGNED PRIMARILY FOR SERVICE IN THE OUTPUT STAGE OF AC-DC RECEIVERS EMPLOYING 150 MA. HEATER TUBES.

## OPERATING CONDITIONS AND CHARACTERISTICS

PLATE VOLTAGE MAX.	110	VOLTS
SCREEN VOLTAGE MAX.	110	VOLTS
GRID VOLTAGE G	-7.5	VOLTS
PEAK AF SIGNAL VOLTAGE	7.5	VOLTS
GRID CIRCUIT RESISTANCE, SELF BIAS	0.75	MEGOMH
AMPLIFICATION FACTOR APPROX.	80	
TRANSCONDUCTANCE	5800	MUMHOS
ZERO-SIGNAL PLATE CURRENT	40	MA.
MAX.-SIGNAL PLATE CURRENT	41	MA.
ZERO-SIGNAL SCREEN CURRENT	3	MA.
MAX.-SIGNAL SCREEN CURRENT	7	MA.
LOAD RESISTANCE	2500	OHMS
DISTORTION		
TOTAL HARMONIC	6.5	PER CENT
SECOND HARMONIC	4.0	PER CENT
THIRD HARMONIC	3.0	PER CENT
POWER OUTPUT	1.5	WATTS

<sup>6</sup> A 150 OHM CATHODE BIAS RESISTOR IS RECOMMENDED FOR CONDITIONS ENCOUNTERED IN AC-DC RECEIVERS.

JETEC DATA  
JOINT ELECTRON TUBE ENGINEERING COUNCIL  
COMMITTEE ON RECEIVING TUBES

Ref. 155B

RCA 135L6GT  
Newark, N.J.  
June 17, 1952  
JUN 2 1958

JETEC TYPE 35L6GT

FILE:

BEAM PENTODE

MECHANICAL DATA

Coated unipotential cathode

Outline drawing.	9-11 or 9-41	Bulb.	T-9
Base . . . . .	B6-81 or B7-7 or B6-84 or B7-59	intermediate shell octal short intermediate shell octal	
Maximum diameter . . . . .			1-9/32"
Maximum overall length . . . . .			3-5/16"
Maximum seated height. . . . .			2-3/4"
Pin connections. . . . .			Basing 7AC
*Pin 1 - No connection		Pin 5 - Grid #1	
Pin 2 - Heater		Pin 7 - Heater	
Pin 3 - Plate		Pin 8 - Cathode, beam plates	
Pin 4 - Grid #2			

\*Pin #1 omitted on Base Nos. B6-81 and B6-84.

Mounting position. . . . . any

ELECTRICAL DATA

Ratings

Heater voltage (ac or dc) . . . . .	35.0	volts
Maximum plate voltage. . . . .	200	volts
Maximum grid #2 voltage. . . . .	125	volts
Maximum plate dissipation. . . . .	8.5	watts
Maximum grid #2 dissipation. . . . .	1.0	watts
Maximum grid #1 circuit resistance:		
Self-bias. . . . .	0.5	megohm
Fixed-bias . . . . .	0.1	megohm
Maximum heater-cathode voltage . . . . .	90	volts

Typical Operating Conditions and Characteristics, Class A1 Amplifier

Heater voltage . . . . .	35.0	35.0	volts
Heater current . . . . .	150	150	ma
Plate voltage .. . . . .	110	200	volts
Grid #2 voltage. . . . .	110	125	volts
Grid #1 voltage. . . . .	-7.5	0	volts
Peak a-f grid #1 voltage . . . . .	7.5	8.0	volts
Cathode-bias resistor. . . . .	0	180	ohms
Plate resistance (approx.) . . . . .	14,000	34,000	ohms
Transconductance . . . . .	5800	6100	$\mu$ hos
Zero-signal plate current. . . . .	40	43	ma
Maximum-signal plate current.. . . . .	41	43	ma
Zero-signal grid #2 current. . . . .	3	2.0	ma
Maximum-signal grid #2 current . . . . .	7	5.5	ma
Load resistance. . . . .	2500	5000	ohms
Total harmonic distortion. . . . .	10	10	%
Power output. . . . .	1.5	3.0	watts

Refer to "Interpretation of Receiving Tube Ratings".