

# 8CS7

## Medium-Mu Dual Triode

### With Dissimilar Units

#### 9-PIN MINIATURE TYPE

#### With Heater Having Controlled Warm-Up Time

*The 8CS7 is the same as the 6CS7 except for the following items:*

Heater Characteristics and Ratings (*Design-Center Values*):

Current . . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	8.4	volts
Warm-up time (Average). . . . .	11	sec

# 8CX8

## Medium-Mu Triode— Sharp-Cutoff Pentode

#### 9-PIN MINIATURE TYPE

#### With Heater Having Controlled Warm-Up Time

*The 8CX8 is the same as the 6CX8 except for the following items:*

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current . . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600 . . . . .	8.0	volts
Warm-up time (Average). . . . .	11	sec

# 8EB8

## High-Mu Triode— Sharp-Cutoff Pentode

#### 9-PIN MINIATURE TYPE

#### With Heater Having Controlled Warm-Up Time

*The 8EB8 is the same as the 6EB8 except for the following items:*

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current . . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600 . . . . .	8.0	volts
Warm-up time (Average). . . . .	11	sec

